TRAK TRL 1845RX Specifications

- Height of Centers 9"
- Distance between centers 45"
- Swing over bed 18.1"
- Swing over saddle wings 17"
- Swing over cross slide 9.13"
- Cross slide travel 10.6"
- Tool section max −1"
- Coolant 13 gal.
- Bed Width 13.4"
- Bed Height 12.4"
- Spindle Nose D1-6
- Spindle through hole 2.36"
- Spindle Taper MT#6
- Spindle diameter front bearing 3.35"
- Number of bearings 2
- Bearing Class (Radial Runout) Normal
- Number of Spindle Speed Ranges 2
- Spindle Speed Range (RPM) 80-850, 250-2500
- Spindle HP 10
- Voltage 200 to 240
- Amps/full load 54
- Machine 200V/3P/60Hz
- Dimensions net LxWxH 88.5x49x61
- Dimensions ship LxWxH 91x52x84
- Weight net 3285
- Weight ship 3800
- Tail stock quill travel 6"
- Quill diameter 2.56"
- Quill taper hole MT#4
- Coolant pump motor 1/8 HP
- Dynamic spindle motor brake
- Way surface hardness 480-560 HB
- Ouiet operation
- Dual sliding doors to control chips and coolant with one door removable
- Meehanite cast monolithic base
- Heavy ribbed base construction
- Bedways hardened and ground
- Sliding surfaces Turcite coated
- Dovetails on cross slide, V-ways on saddle
- Adjustable saddle gibs
- Maximum rapid 400 ipm z axis

Control Specifications

- Two-axis CNC, two-axis DRO
- Electronic Handwheels for manual operation
- 15.6" LCD with Touchscreen

- Intel® 2.0 GHz processor
- 4 GB Ram
- At least 32GB of mSATA SSD
- 5 USB connectors
- 2 Ethernet Ports (1 for user and 1 for control system)
- Override of program feedrate
- Override of spindle speed
- LED status lights built into run panel
- E-stop
- Spindle Control (FWD, REV, OFF)
- Feed STOP and GO
- Fine vs Course EHW resolution control
- Accessory button to control coolant and AUTO mode in RUN mode
- Power Reset Button
- Jogstick for convenient jog

Computer Module Control Hardware

- 2 axis motor control X and Z axis, Axis to control CNC Turret
- 14 inputs
- 9 outputs

Software Features – general operation

- Clear, uncluttered screen display
- Prompted data inputs
- English language no codes
- Soft keys change within context
- Windows® operating system
- Selectable two or three-axis CNC
- Color graphics with adjustable views
- Gestures for pan, zoom, rotate
- Inch/mm selectable
- Convenient modes of operation
- Networking

Info Softkeys

- Status
- Tool Table
- EPA
- Math Help
- Warnings
- Defaults
- Keyboard
- Calculator

DRO Mode features for manual machining

Incremental and absolute dimensions

- Powerfeed X or Z
- GO TO
- Do One Tapers for any angle
- Do One Radius
- Do One Fillet
- Thread Repair (O)
- MAX RPM set maximum RPM for spindle to run
- Servo motion to return to home
- Tool offsets from library
- Spindle speed setting with override

Program Mode features

- Geometry-based programming
- Incremental and absolute dimensions
- Automatic tool nose radius cutter compensation
- Circular interpolation
- Linear interpolation
- Look –graphics at all times
- List step graphics with programmed events displayed
- Alphanumeric program names
- Canned Cycles
- Program data editing
- Options within events
- Math helps with graphical interface
- Subroutine repeat of programmed events
- Nesting
- Programmable spindle speeds

Canned Cycles

- Position
- Drill
- Bore
- Turn
- Arc
- Cycle
- Thread
- Groove
- Tap (O)
- Cut Off

Edit mode Features

- Delete events
- Search Edit (O)
- Erase program

- G Code Editor (O)
- Clip Board (O)

Set Up Mode Features

- Program Diagnostics
- Software travel limits
- Tool path graphics with adjustable views
- Verify Software
- Service Codes
- CNC Turret Homing
- Advanced Diagnostics routines

Run Mode Features

- 3D CAM file program run
- 3D G code file run with tool comp
- Real time run graphics with tool icon

Program In/Out Mode Features

- Simple program storage to USB device or Network
- CAM program converter
- Converter for prior-generation ProtoTRAK programs
- Open and Save Temp Feature
- Cut, Copy, Delete, Paste of program(s)
- Creating folders
- Program Look preview of files

Advanced Features Option - Lathes

- Gang tool operation
- Custom thread
- Tap
- Event comments
- Thread repair
- Verify Make Part feature
- Clipboard
- G Code Edit
- Search Edit