# TRAK TRL 3060RX Lathe Specifications with the ProtoTRAK RLX Control



# **Machine Specifications**

- Height of Centers 16.5"
- Distance between centers 60"
- Swing over bed 33"
- Swing over saddle wings 33"
- Length of gap 15.5"
- Swing over gap 43.5"
- Swing over cross slide 21.2"
- Maximum cutting length –60"
- Cross slide travel 20.5"
- Tool section max 1.5"
- Coolant Reservoir 35.6 gallons
- Coolant pump motor 1/4 HP
- Bed Width 18"
- Bed Height 15.75"
- Spindle Nose A2-11
- Spindle through hole 6.3"
- Spindle Taper Non-Standard Taper in Spindle
- Taper in reduction sleeve MT #6
- Spindle diameter front bearing (ID) 7.87"
- Number of bearings 2
- Number of Spindle Speed Ranges 2
- Spindle Speed Range (RPM) L: 20-415, H: 40-1300
- Spindle HP 30
- Voltage 480
- Amps/full load 62
- Frequency 60 Hz
- Dimensions net LxWxH 150.31" x 86.61 x 85.87"
- Dimensions ship LxWxH 162" x 90.55 x 93.87"
- Weight net 13970 lbs.

Rev: 4/3/2024

- Weight ship 14270 lbs.
- Tail stock quill travel 8"
- Quill diameter 4.13"
- Quill taper hole MT #6
- Dynamic spindle motor brake
- Way surface hardness 480-560 HB
- Quiet operation
- Meehanite cast monolithic base
- Heavy ribbed base construction
- Bedways hardened and ground
- Sliding surfaces Turcite coated
- Dovetails on cross slide, V-ways on saddle
- Adjustable saddle gibs
- Maximum rapid 400 ipm on z-axis, 200 ipm on x-axis

# **ProtoTRAK RLX System Specifications**

#### **Pendant Control Hardware**

- Two-axis CNC, two-axis DRO
- Electronic Handwheels for manual operation
- 15.6" LCD with Touchscreen
- Intel® 2.0 GHz processor
- 4 GB Ram
- At least 32GB of mSATA SSD
- 5 USB connectors
- 2 Ethernet Ports (1 for user and 1 for control system)
- Override of program feedrate
- Override of spindle speed
- LED status lights built into run panel
- E-stop
- Spindle Control (FWD, REV, OFF)
- Feed STOP and GO
- Fine vs Course EHW resolution control
- Accessory button to control coolant and AUTO mode in RUN mode
- Power Reset Button
- Jogstick for convenient jog

### **Software Features – General Operation**

- Clear, uncluttered screen display
- Prompted data inputs
- English language no codes
- Soft keys change within context
- Windows® operating system
- Selectable two or three-axis CNC
- Color graphics with adjustable views
- Gestures for pan, zoom, rotate
- Inch/mm selectable
- Convenient modes of operation
- Networking

#### **Info Softkeys**

- Status
- Tool Table
- EPA

- Math Help
- Warnings
- Defaults
- Kevboard
- Calculator

## **DRO Mode Features for Manual Machining**

- Incremental and absolute dimensions
- Powerfeed X or Z
- GO TO
- Do One Tapers for any angle
- Do One Radius
- Do One Fillet
- Thread Repair (O)
- MAX RPM set maximum RPM for spindle to run
- Servo motion to return to home
- Tool offsets from library
- Spindle speed setting with override
- Spindle JOG and HOLD feature

#### **Program Mode Features**

- Geometry-based programming
- Incremental and absolute dimensions
- Automatic tool nose radius cutter compensation
- Circular interpolation
- Linear interpolation
- Look graphics at all times
- List step graphics with programmed events displayed
- Alphanumeric program names
- Canned Cycles
- Program data editing
- Options within events
- Math helps with graphical interface
- Subroutine repeat of programmed events
- Nesting
- Programmable spindle speeds

#### **Canned Cycles**

- Position
- Drill
- Bore
- Turn
- Arc
- Cycle
- Thread
- Groove
- Tap (O)
- Cut Off

#### **Edit Mode Features**

- Delete events
- Search Edit (O)
- Erase program
- G Code Editor (O)

• Clip Board (O)

#### **Set Up Mode Features**

- Program Diagnostics
- Software travel limits
- · Tool path graphics with adjustable views
- Verify Software
- Service Codes
- CNC Turret Homing
- Advanced Diagnostics routines

#### **Run Mode Features**

- CAM file program run
- G code file run with tool comp
- Real time run graphics with tool icon

#### **Program In/Out Mode Features**

- Simple program storage to USB device or Network
- CAM program converter
- Converter for prior-generation ProtoTRAK programs
- Open and Save Temp Feature
- Cut, Copy, Delete, Paste of program(s)
- Creating folders
- Program Look preview of files

## **Advanced Features Option – Lathes**

- Gang tool operation
- Custom thread
- Tap
- Event comments
- Thread repair
- Verify Make Part feature
- Clipboard
- G Code Edit
- Search Edit

Rev: 4/3/2024