PREVENTATIVE MAINTENANCE	
TRAK TOOLS 28-POINT LATHE CHECKLIST	
Southwestern industries, inc.	
SERVICE DATE:	/ / SUPPORT TICKET #:
COMPANY:	#:
SERIAL #:	MODEL:
Complete form	by placing a checkmark in the bayes as tack are completed
	by placing a checkmark in the boxes as task are completed.
1	Update software when applicable. Verify Error Logging is turned on (Code 319) for SLX & RLX.
2	Check and adjust level of machine.
3	Fill lube pump. Manually pump oiler and check lube points.
4	Run spindle throughout all gear ranges and RPM's. Note any unusual noises below.
5	Check spindle preload and record value: inlbs.
6	Check alignment X & Z ballscrew.
7	Check drive train assemblies.
8	Use jogstick and turn electronic handwheels. Listen for unusual noises. Note any problems below.
9	Check and adjust spindle motor mounting and belt as needed. Inspect belt.
10	Change headstock gearbox oil if requested (Customer to provide oil).
11	Check spindle brakes. Spindle stop? Yes No (1440 & 1745 models: Check Setting of timer)
12	Inspect Electronic Handwheels, Clean friction pucks as needed.
13	Check alignment of spindle encoder. Inspect encoder coupling.
14	Inspect and adjust X and Z axis servo motor belts.
15	Adjust Gibs and Run Service Codes 12 and 100. (Service Codes 12 & 100 not applicable to RLX products)
16	Calibrate X and Z-axis and check backlash. Record backlash values below.
17	Record Positional accuracy: X: Z:
18	Record Uni-directional repeatability: X: Z:
19	Record Bi-directional repeatability: X: Z:
20a	Run Code 131: Disable Electronic Handwheels.
20b	Run Code 132: Electronic Handwheel test.
20c	Run Code 133: Spindle Encoder test.
21	Check if emergency stop buttons disable Handwheels, Jogsticks, and Spindle.
22	Check all cables and cable connections. All cables should be neat and securely tied.
23	Check coolant pump operation.
24	Inspect way wipers and note the condition.
25	Check headstock alignment. Cut test part. Check for taper. Taper Over 6"
26	
27	
28	Replace Pendant fan filter (N/A on RLX products).
20	Wipe down machine. Clean touchscreen on RLX products.
List potential problems, observations, or recommendations:	

TECHNICIAN

F10232 REV041719